
1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name PROSHINE CERAMIC TOTAL BODY PROTECTANT
Synonyms CERAMIC TOTAL BODY PROTECTANT • RUST-OLEUM CERAMIC TOTAL BODY PROTECTANT

1.2 Uses and uses advised against

Uses PAINT PROTECTANT • PROTECTANT

1.3 Details of the supplier of the product

Supplier name DUBOIS CHEMICALS AUSTRALIA PTY LTD
Address 13 - 15 Flight Drive, Tullamarine, VIC, 3043, AUSTRALIA
Telephone +61 3 8340 3200
Fax +61 3 8340 3247
Website <https://www.prowash.com.au/>

1.4 Emergency telephone numbers

Emergency 13 11 26 (Poisons Information Centre)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Not classified as a Physical Hazard

Health Hazards

Skin Corrosion/Irritation: Category 2
Serious Eye Damage / Eye Irritation: Category 1

Environmental Hazards

Not classified as an Environmental Hazard

2.2 GHS Label elements

Signal word DANGER

Pictograms**Hazard statements**

H315 Causes skin irritation.
H318 Causes serious eye damage.

Prevention statements

P264 Wash thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

PRODUCT NAME PROSHINE CERAMIC TOTAL BODY PROTECTANT**Response statements**

P302 + P352	IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P321	Specific treatment is advised - see first aid instructions.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Storage statements

None allocated.

Disposal statements

None allocated.

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE (REFINED)	64742-46-7	265-148-2	10 to 20%
1-BUTOXY-2-PROPANOL	5131-66-8	225-878-4	1 to 5%
2-BUTOXYETHANOL	111-76-2	203-905-0	1 to 5%
ISOPROPYL ALCOHOL	67-63-0	200-661-7	1 to 5%
MODIFIED SILOXANE	71750-79-3	615-336-9	1 to 5%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	Remainder
QUATERNARY AMMONIUM COMPOUNDS, DICOCO ALKYL DIMETHYL, CHLORIDES	61789-77-3	263-087-6	10 to 20%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting. Rinse mouth out with water and give plenty of water to drink.
First aid facilities	Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve carbon oxides and hydrocarbons when heated to decomposition.

PRODUCT NAME PROSHINE CERAMIC TOTAL BODY PROTECTANT

5.3 Advice for firefighters

Treat as per requirements for surrounding fires. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

None allocated.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Store removed from direct sunlight.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
2-Butoxyethanol (EGBE)	SWA [AUS]	20	96.9	50	242
2-Butoxyethanol (EGBE)	SWA [Proposed]	10	49	50	242
Isopropyl alcohol	SWA [AUS]	400	983	500	1230
Isopropyl alcohol	SWA [Proposed]	200	491	400	984
Mineral Oil Mist	SWA [AUS]	--	5	--	--

Biological limits

Ingredient	Determinant	Sampling Time	BEI
2-BUTOXYETHANOL	Butoxyacetic acid (BAA) in urine (with hydrolysis)	End of shift	200 mg/g creatinine
ISOPROPYL ALCOHOL	Acetone in urine	End of shift at end of workweek	40 mg/L

Reference: ACGIH Biological Exposure Indices

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.

PRODUCT NAME PROSHINE CERAMIC TOTAL BODY PROTECTANT

PPE

Eye / Face	Wear splash-proof goggles.
Hands	Wear PVC or rubber gloves. With prolonged use, wear viton® or nitrile gloves.
Body	With prolonged use, wear coveralls.
Respiratory	Where an inhalation risk exists, wear a Type A (Organic vapour) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	CLEAR GREEN LIQUID
Odour	SLIGHT FRUITY ODOUR
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
pH	4.36
Vapour density	NOT AVAILABLE
Relative density	0.936
Solubility (water)	SOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	28 mPa·s @ 20°C
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites).

10.6 Hazardous decomposition products

May evolve carbon oxides and hydrocarbons when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met. Acute exposure may result in nausea,

PRODUCT NAME PROSHINE CERAMIC TOTAL BODY PROTECTANT

vomiting, abdominal pain, diarrhoea, dizziness and drowsiness.

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE (REFINED)	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)	> 2.53 mg/L (rat)
1-BUTOXY-2-PROPANOL	5660 uL/kg (rat)	3100 mg/kg (rabbit)	--
2-BUTOXYETHANOL	470 mg/kg (rat)	220 mg/kg (rabbit)	450 mg/L/4hrs (rat)
ISOPROPYL ALCOHOL	> 2000 mg/kg (rat) (AICIS)	> 2000 mg/kg (rat) (AICIS)	> 20 mg/L (rat) (AICIS)

Skin	Causes skin irritation. Contact may result in irritation, redness, pain and rash.
Eye	Causes serious eye damage. Contact may result in irritation, lacrimation, pain, redness and possible serious eye damage.
Sensitisation	Not classified as causing skin or respiratory sensitisation.
Mutagenicity	Not classified as a mutagen.
Carcinogenicity	Not classified as a carcinogen. Highly refined mineral oils are not classifiable as to its carcinogenicity in humans (IARC Group 3).
Reproductive	Not classified as a reproductive toxin.
STOT - single exposure	Not classified as causing organ damage from single exposure. Due to product form / nature of use, an inhalation hazard is not anticipated with normal use. However, if product is heated or mists generated, exposure may result in respiratory irritation, headache and nausea.
STOT - repeated exposure	Not classified as causing organ damage from repeated exposure.
Aspiration	Aspiration into the lungs may result in chemical pneumonitis and pulmonary oedema.

12. ECOLOGICAL INFORMATION**12.1 Toxicity**

This product can float on water, restricting oxygen exchange with possible asphyxiation of aquatic life.

12.2 Persistence and degradability

Expected to be inherently biodegradable.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

Low solubility and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

12.5 Other adverse effects

Mineral oils biodegrade slowly and should not be released to waterways or soil. They can float on water, restricting oxygen exchange with possible asphyxiation of aquatic life.

13. DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods**

Waste disposal Reuse where possible or return to manufacturer/supplier. May be recycled. Do not release to drains or waterways. Contact the manufacturer/supplier for additional information (if required).

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

PRODUCT NAME PROSHINE CERAMIC TOTAL BODY PROTECTANT

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None allocated.	None allocated.	None allocated.
14.2 Proper Shipping Name	None allocated.	None allocated.	None allocated.
14.3 Transport hazard class	None allocated.	None allocated.	None allocated.
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

Not a Marine Pollutant.

14.6 Special precautions for user

Hazchem code	None allocated.
--------------	-----------------

15. REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Poison schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Classifications	Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).
Inventory listings	AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals) All components are listed on AIIC, or are exempt. UNITED STATES: TSCA (US Toxic Substances Control Act) All components are listed on the TSCA inventory, or are exempt.

16. OTHER INFORMATION

Additional information	<p>MINERAL OILS - SOLVENT REFINED: Animal experiments and human experience have not shown cancer risks when handling solvent refined mineral oils, unlike non refined mineral oils. CLEANING MINERAL OIL CONTAMINATED CLOTHING: Cleaners are advised that when cleaning oil contaminated clothing it is essential that freshly distilled solvent is used for each batch, including final rinse, as even filtered solvent will leave oil residues.</p> <p>RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.</p> <p>PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.</p> <p>HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.</p>
-------------------------------	---

PRODUCT NAME PROSHINE CERAMIC TOTAL BODY PROTECTANT**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmtglobal.com

[End of SDS]